



## Updated 2020 Restoration Allocation & Default Flow Schedule

March 20, 2020

### Introduction

The following transmits an updated 2020 Restoration Allocation and Default Flow Schedule to the Restoration Administrator for the San Joaquin River Restoration Program (SJRRP), consistent with the January 2020 (version 2.1) Draft Restoration Flow Guidelines (Guidelines). This Restoration Allocation and Default Flow Schedule provides the following:

- Forecasted water year Unimpaired Inflow: the estimated flows that would occur absent regulation on the river. This value is also known as the “Natural River” or “Unimpaired Runoff” or “Full Natural Flow,” and is utilized to identify the water year type.
- Hydrograph Volumes: the annual allocation hydrograph based on water year unimpaired inflow, utilizing Method 3.1 with the Gamma Pathway (RFG-Appendix C, Figure C3) agreed to by the Parties in December 2008.
- Default Flow Schedule: the schedule of Restoration Flows in the absence of a recommendation from the Restoration Administrator.
- Additional Allocations: the hypothetical Restoration Allocations that would result from 10%, 50%, 75%, and 90% probability of exceedance Unimpaired Inflow forecast.
- Unreleased Restoration Flows: the amount of Restoration Flows not released due to channel capacity constraints, without delaying completion of Phase 1 improvements.
- Flow targets at Gravelly Ford: the flows at the head of Reach 2, and estimated scheduled releases from Friant Dam adjusted for the assumed Holding Contract demands and losses in Exhibit B.
- Restoration Budget: the volumes for the annual allocation, spring flexible flow, base flow, riparian recruitment, and fall flexible flow.
- Remaining Flexible Flow Volume: the volume of Restoration Flows released and the remaining volume available for flexible scheduling.
- Operational Constraints: the flow release limitations based on downstream channel capacity, regulatory, or legal constraints.

Consistent with Paragraph 18 of the Settlement, the Restoration Administrator shall make recommendations to the Secretary of the Interior concerning the manner in which the hydrographs shall be implemented. As described in the Guidelines, the Restoration Administrator is requested to recommend a flow schedule showing the use of the entire annual allocation during the upcoming Restoration Year, categorize all recommended flows by account, and recommend both an unconstrained and capacity limited recommendation. If either an unconstrained recommendation or a capacity limited recommendation is not provided by the Restoration Administrator, the Capacity Constrained Default Flow Schedule (Table 6b) will be implemented.

The Restoration Administrator is requested to provide an updated recommendation and flow schedule by April 1, 2020.

## **Forecasted Unimpaired Inflow**

Unimpaired Runoff represents the natural water production of a river basin, unaltered by upstream diversions, storage, or by export or import of water to or from other watersheds (a.k.a. “Unimpaired Inflow” or “Natural River” or “Full Natural Flow”). It is calculated for the period of a water year. The forecast of the Unimpaired Runoff determines the volume of Restoration Flows available for the Restoration Year (i.e. the Restoration Allocation). Information for forecasting the Unimpaired Runoff includes:

- Observation of Unimpaired Runoff into Millerton Lake to support the water supply allocation<sup>1</sup>;
- The California Department of Water Resources (DWR) Bulletin 120 latest update for San Joaquin River inflow to Millerton Lake Unimpaired Flow, and/or the most current DWR Bulletin Water Supply Index (WSI)<sup>3</sup>;
- The National Weather Service (NWS) Ensemble Streamflow Prediction (ESP) Water Supply Forecast for the San Joaquin River at Millerton Lake<sup>5</sup>.
- Other forecast models, ground-based observations, remotely-sensed observations, hydrologic models, analysis of historic patterns, and short-term weather forecasts as appropriate.

Table 1 shows the water year 2020 (October 1, 2019 to September 30, 2020) observed accumulated and forecasted water year Unimpaired Inflows at Millerton Lake. This table also includes the published DWR forecast, the DWR forecast adjusted for an expected runoff for the current month, the NWS forecast with and without a 7-day smoothing function applied to remove the day-to-day variance, and the NWS forecast with 7-day smoothing and adjustment for the runoff for the current month. Figure 1a plots DWR and NWS forecast values over the entire water year, while Figure 1b shows the most recent period in detail.

**Table 1 — San Joaquin River Water Year Actuals and Forecasts at Millerton Lake, in Thousands of Acre-Feet (TAF)**

	Forecast Exceedance Percentile				
	90%	75%	50%	25%	10%
Accumulated Unimpaired Runoff (“Natural River”) March 19, 2020 <sup>1</sup>	169.4 TAF				
Accumulated Unimpaired Runoff as percent of normal <sup>2</sup>	39%				
DWR, March 17, 2020 <sup>3</sup> (Published Value)	550 TAF	630 TAF <sup>7</sup>	705 TAF	780TAF <sup>7</sup>	850 TAF
DWR, March 17, 2020 <sup>4</sup> (Runoff Adjusted)	574 TAF	643 TAF <sup>7</sup>	711 TAF	775 TAF <sup>7</sup>	838 TAF
NWS, March 18, 2020 (Published Daily Value <sup>5</sup> )	627 TAF	746 TAF	842 TAF	991 TAF	1,320 TAF
Smoothed NWS, March 18, 2020 (7-day Smoothing <sup>6</sup> )	579 TAF	668 TAF	795 TAF	967 TAF	1,343 TAF
Smoothed NWS, March 18, 2020 (Runoff Adjusted <sup>4</sup> )	599 TAF	684 TAF	805 TAF	969 TAF	1,334 TAF

<sup>1</sup> <http://www.usbr.gov/mp/cvo/vungvari/milfln.pdf>

<sup>2</sup> Based on average accumulation of Unimpaired Runoff

<sup>3</sup> B120: <http://cdec.water.ca.gov/cgi-progs/iodir?s=b120>, or B120 Update: [http://cdec.water.ca.gov/cgi-progs/iodir\\_ss/b120up](http://cdec.water.ca.gov/cgi-progs/iodir_ss/b120up), or WSI: <http://cdec.water.ca.gov/cgi-progs/iodir/WSI.2017>


<sup>4</sup> The adjusted data has been updated with the actual unimpaired inflow through the current date and projected out for the remainder of the month.

<sup>5</sup> [http://www.cnrfc.noaa.gov/water\\_resources\\_update.php?stn\\_id=FRAC1&stn\\_id2=FRAC1&product=WaterYear](http://www.cnrfc.noaa.gov/water_resources_update.php?stn_id=FRAC1&stn_id2=FRAC1&product=WaterYear)


<sup>6</sup> The NWS smoothed data uses a 7-day triangular weighted moving average, where the most recent day (n) is given greater weight than each previous forecast day (n-1, 2, 3, etc.); this reduces noise stemming from ESP model input. The following formula is used:  $((Forecast_n * 1) + (Forecast_{n-1} * 0.857) + (Forecast_{n-2} * 0.714) + (Forecast_{n-3} * 0.571) + (Forecast_{n-4} * 0.429) + (Forecast_{n-5} * 0.286) + (Forecast_{n-6} * 0.143)) / 4$

<sup>7</sup> These are interpolated values as the complete DWR forecast was not available with the most recent issuance

The 2020 Water Year has so far produced far less than normal runoff (39%). Daily Unimpaired Runoff values are currently equivalent to what would be expected in the low range of a Dry Water Year Type (about 715 TAF), yet they continue to gradually decline. Runoff ratio to date is currently 46%, calculated by measured Unimpaired Runoff divided by modeled Surface Water Input (also known as watershed yield, this statistic tracks the fraction of water reaching the soil surface that produces runoff). Because the runoff ratio to date (46%) is slightly higher than the percent of normal runoff (39%), one can infer that the antecedent moisture conditions in the watershed are somewhat higher due to the previous wet year.




**Figure 1a — Plot of 2020 Water Year forecasts, including both NWS Ensemble Streamflow Prediction Forecasts and DWR Forecasts**



**Figure 1b — Detail plot of most recent forecasts**

The DWR Bulletin 120 water supply forecast for the San Joaquin above Millerton Lake has been steadily falling over the past several weeks, even the 90% exceedance forecast. For the first time this water year, the DWR forecast has fallen below the Ensemble Streamflow Prediction values published by the National Weather Service. Reclamation continues to hold the opinion that in the San Joaquin the NWS is currently the more accurate forecast. In fact, the NWS forecast may still be underestimating the volume of available snow as was suspected over the past two months. This suspected bias is somewhat mitigated by the fact that the NWS forecast incorporates expected precipitation over the next 16 days, and also because the NWS forecast has a tendency toward overestimating runoff after peak snow water equivalent (SWE) is reached.

This allocation issuance follows a significant storm event which increased snowpack at high elevations by roughly 1/3<sup>rd</sup> and extended the snow-covered area from 7,000' elevation to 4,500' elevation (Figure 2). Rain and snow accumulation was highly variable during this 5-day storm event, with some sites picking up barely 1" of precipitation while others exceeded 5"; a mean value across the watershed is estimated at 3.5" of SWE.



**Figure 2 — NOHRSC model of SWE comparing pre-storm (left) and post-storm (right).**

Four snowpack models were available between March 13 and March 18. Agreement between the models has declined somewhat, though one must recognize that the CU Boulder product did not incorporate any of the last storm event and the ARS product did not incorporate the final day of the storm event. Reclamation has consensus value of 640 TAF snowpack Snow Water Equivalent (SWE) given past model performance and snow pillow measurements. Airborne Snow Observatory (ASO) data is expected to be available prior to the April 10-20 allocation issuance. The distribution of SWE modeled by ARS iSnobal is shown in Figure 3.


**Table 2 — Total snowpack volume (TAF of Snow Water Equivalent) depicted by four models and a consensus estimate for March 18, 2020.**

Date	CNRFC	NOHRSC	CU Boulder	ARS iSnohal	ASO	Reclamation Consensus
Snow Water Equivalent Volume (TAF)	600	589	502 <sup>8</sup>	548 <sup>9</sup>	N/A <sup>10</sup>	<b>640</b>

<sup>8</sup> CU Boulder "Real-time SWE" model was dated March 13


<sup>9</sup> USDA-ARS "iSnohal" model was dated March 16

<sup>10</sup> First ASO surveys of 2020 are expected to be available April 1



**Figure 3 — iSnohal model output from March 16.** The most recent storm added substantially to the mid-elevations and brought snow down to 5000'. Snowpack cold-content and snow surface albedo have increased also. This model run did not capture the entire storm as precipitation was still occurring as the time the model period ended.

Should no further precipitation occur, Reclamation expects that annual runoff would total between 570 and 620 TAF. However, the long-term weather models out 16 days depict above normal precipitation. This forecast is supported by a Madden-Julian Oscillation and an Arctic Oscillation (two climate patterns that affect worldwide weather) that are both favorable for California storms. Most model runs of both the GFS "American" model and the ECMWF "Euro" model are showing 1.5-2.5" of precipitation for the San Joaquin over the next 10 days with a chance of additional precipitation during the 10-16 day window. If this forecast materializes, one would expect all forecast exceedances to rise approximately 90 TAF.



**Figure 3 — 10-day cumulative precipitation** shown for the American model (left) and European model (right). Both model runs depict in excess of 2” of precipitation for the San Joaquin watershed.

## Combining Forecasts

Staff from the South-Central California Area Office of Reclamation and SJRRP jointly track and evaluate the accuracy of runoff forecasts on a regular basis. Based on the age of these forecasts, the short-term and long-term weather forecasts, the climatological outlook, observed Unimpaired Inflow, and other available information, a hybrid forecast is generated. The weighting of the different components is regularly evaluated and selected using professional judgment and the best available information. **For the current allocation, the DWR “runoff adjusted” and NWS “smoothed runoff adjusted” forecasts are combined with a 10/90 blending respectively.** This results in the Hybrid Unimpaired Inflow Forecasts shown in Table 3.

**Table 3 — Current Blending and Hybrid Unimpaired Inflow Forecast**

	Forecast Probability of Exceedance using blending				
	90%	75%	50%	25%	10%
Blending Ratio (DWR/NWS)	10/90				
Hybrid Unimpaired Inflow Forecast (TAF)	579	670	796	957	1,306

This blending produced on March 18 was chosen based on the historic performance of the DWR and NWS forecasts during this time of the year, the accuracy of these forecasts in predicting monthly unimpaired inflow over the recent months, snow measurements and snowpack models, application of hypothetical runoff ratios, the long-range forecast, historic analogs, the seasonal

climate outlook, the age of the forecasts, and other performance factors. This blending has important consequences since the 75% exceedance lies just above the threshold of Critical-High and Dry year types and the associated 85 TAF difference in allocation. Despite the sensitivity of the allocation to the blending procedure, Reclamation believes that the current water year type will hold until the next allocation issuance in April. Note that the “NWS smoothing” function that is applied to their daily forecast as shown in Table 1 and Figure 1 dampens the fluctuations in the forecast and provides greater confidence during a rapid upswing. Should the blended forecast decline below the threshold at the Critical-High/Dry boundary, a new allocation update will be promptly issued.

## Restoration Allocation

As per the draft Guidelines, the **75% exceedance** forecast is used for the allocation under current hydrologic conditions to set the Restoration Flow Allocation. Table 4 below, from the Guidelines version 2.1, depicts the progression of forecast exceedance used to set the Restoration Allocation.

**Table 4 — Guidance on Percent Exceedance Forecast to Use for Allocation**

	Value (TAF)	Date of Forecast Used for the Allocation					
		January	February	March	April	May	June
<b>If the 50% forecast is:</b>	Above 2200	50	50	50	50	50	50
	1600 to 2200	75	75	50	50	50	50
	900 to 1599	75	75	75	50	50	50
	500 to 899	90	90	75	50	50	50
	Below 500	90	90	90	90	75	50

Applying the 10/90 forecast blending determined by Reclamation and, using the 75% exceedance forecast dictated by the Guidelines, Reclamation calculates an **Unimpaired Inflow hybrid forecast of 670 TAF** and a **Dry Water Year Type**. This provides a **Restoration Allocation of 155.335 Thousand Acre-Feet (TAF)** as measured at Gravelly Ford (GRF).

Combined with Holding Contracts on the San Joaquin River, this equates to a **Friant Dam Release of 272.280 TAF**. Other hypothetical allocations are presented in Table 5 as grayed values and indicate the range of probable forecasts and the resulting Restoration Allocation.



**Table 5 — SJRRP Water Year Type and Allocation for 2020 Restoration Year Shown with Other Hypothetical Values in Gray**

	Forecast Probability of Exceedance using proposed blending				
	90%	75%	50%	25%	10%
Hybrid Unimpaired Inflow Forecast (TAF)	579	<b>670</b>	796	957	1,306
Water Year Type	Critical-High	<b>Dry</b>	Dry	Normal-Dry	Normal-Dry
Restoration Allocation at GRF (TAF)	70.919	<b>155.335</b>	183.452	216.989	263.970
Friant Dam Flow Releases (TAF)	187.785	<b>272.280</b>	300.397	333.935	380.915

Note that the current allocation is based on the draft January 2020 Restoration Flow Guidelines (version 2.1), yet the current allocation would be identical under the previous February 2018 Guidelines (version 2.0).

## Default Flow Schedule

The Default Flow Schedule, derived from Exhibit B in the Settlement, identifies how Reclamation will schedule the Restoration Allocation for the current Water Year Type and Unimpaired Inflow volume absent a recommendation from the Restoration Administrator. The Guidelines provide detail on how a Default Flow Schedule is parsed from the allocation volume. This approved method of distributing water throughout the year is referred to as “Method 3.1” with the “gamma pathway.”

### *Exhibit B Method 3.1 Default Flow Schedules*

Table 6a shows the “Basic” Default Flow Schedule flows and corresponding Restoration Allocation volumes for the entire year absent channel capacity constraints, including total releases from Friant Dam and Restoration Flows releases in excess of Holding Contracts. Volume is distributed as various flow rates across the year as per the methods explained in the Restoration Flow Guidelines.

Table 6b shows the Default Flow Schedule volumes with all expected operational constraints, primarily controlled by seepage limitations in Reach 4A. Any volume within the Spring Flexible Flow Account and Fall Flexible Flow Account that cannot be released on the default schedule is shifted to times with available capacity as per the Guidelines. This Capacity Constrained Default Flow Schedule depicted in Table 6b will be implemented in the absence of a specific recommendation by the Restoration Administrator. With these known constraints, a Restoration Flow volume of **0 TAF** is generated that cannot be scheduled for release without a Water Supply Test. This volume would become Unreleased Restoration Flows (URFs) under the Capacity Constrained Default Flow Schedule. This is an estimated volume of water, actual URF volumes will depend on several factors including the Restoration Administrator Recommendation, recapture of Restoration Flows at Mendota Pool, and real-time assessments of groundwater constraints.

**Table 6a — Basic Default Flow Schedule**

Flow Period	Flow (cfs)				Volume (TAF)	
	Friant Dam Release	Holding Contracts <sup>11</sup>	Flow Target at GRF	Restoration Flow at GRF	Friant Dam Release	Restoration Flow at GRF
Mar 1 – Mar 15	500	130	375	370	14.876	11.008
Mar 16 – Mar 31	1500	130	1375	1370	47.603	43.478
Apr 1 – Apr 15	350	150	205	200	10.413	5.950
Apr 16 – Apr 30	326	150	181	176	9.709	5.246
May 1 – May 28	260	190	75	70	14.440	3.888
May 29 – Jun 30	260	190	75	70	17.018	4.582
July 1 – July 29	260	230	35	30	14.955	1.726
Jul 30 – Aug 31	260	230	35	30	17.018	1.964
Sep 1 – Sep 30	350	210	145	140	20.826	8.331
Oct 1 – Oct 31	350	160	195	190	21.521	11.683
Nov 1 – Nov 6	400	130	275	270	4.760	3.213
Nov 7 – Nov 10	350	130	225	220	2.777	1.745
Nov 11 – Nov 30	350	120	235	230	13.884	9.124
Dec 1 – Dec 31	350	120	235	230	21.521	14.142
Jan 1 – Jan 31	350	100	255	250	21.521	15.372
Feb 1 – Feb 28	350	100	255	250	19.438	13.884
<b>Totals</b>					<b>272.280</b>	<b>155.335</b>

**Table 6b — Capacity Constrained Default Flow Schedule**

Flow Period	Flow (cfs)				Volume (TAF)		
	Friant Dam Release	Holding Contracts <sup>11</sup>	Flow Target at GRF	Restoration Flow at GRF	Friant Dam Release	Restoration Flow at GRF	Unreleased Restoration Flow <sup>12</sup>
Mar 1 – Mar 15	525	130	400	395	15.620	11.752	-0.744
Mar 16 – Mar 31	525	130	400	395	16.661	12.536	30.942
Apr 1 – Apr 15	545	150	400	395	16.215	11.752	-5.802
Apr 16 – Apr 30	545	150	400	395	16.215	11.752	-6.506
May 1 – May 28	582	190	397	392	32.330	21.778	-17.890
May 29 – Jun 30	260	190	75	70	17.018	4.582	0
July 1 – July 29	260	230	35	30	14.955	1.726	0
Jul 30 – Aug 31	260	230	35	30	17.018	1.964	0
Sep 1 – Sep 30	350	210	145	140	20.826	8.331	0
Oct 1 – Oct 31	350	160	195	190	21.521	11.683	0
Nov 1 – Nov 6	400	130	275	270	4.760	3.213	0
Nov 7 – Nov 10	350	130	225	220	2.777	1.745	0
Nov 11 – Nov 30	350	120	235	230	13.884	9.124	0
Dec 1 – Dec 31	350	120	235	230	21.521	14.142	0
Jan 1 – Jan 31	350	100	255	250	21.521	15.372	0
Feb 1 – Feb 28	350	100	255	250	19.438	13.884	0
<b>Totals</b>					<b>282.280</b>	<b>155.335</b>	<b>0</b> <sup>12</sup>

<sup>11</sup> In recent years, Holding Contract demands have been higher than assumed under Exhibit B of the Settlement, in which case, flows at Friant are increased to achieve the Gravelly Ford Flow Target.

<sup>12</sup> This estimate of URF volume is based on the most constraining reach, with Spring Flexible Flows redistributed March 1 through May 28 as necessary and Fall Flexible Flows redistributed Sept 3 through December 28 as necessary up to channel capacity constraints. Actual URF volume will depend on the Restoration Administrator's recommendations.

### ***Exhibit B Restoration Flow Budget***

Table 7 shows the components of the annual water budget for March 1, 2020, through February 28, 2021 (i.e. the Restoration Year). The Continuity Flow Account, Spring Flexible Flow Account, Riparian Recruitment Flow Account, and Fall Flexible Flow Account reflect the Exhibit B hydrograph for the current Restoration Allocation. The expected 116.945 TAF for Holding Contracts is shown. The volume for each flow account may change with subsequent Restoration Allocations.

**Table 7 — Restoration Budget with Flow Accounts**

Period	Holding Contract Demand (TAF)	Restoration Flows			
		Continuity Flow Account	Spring Flexible Flow	Riparian Recruitment Flows	Fall Flexible Flows
Feb 1 – Feb 28	–	0	40.959 (Feb 1 – May 38)	–	–
Mar 1 – Apr 30	16.920	24.723		–	–
May 1 – May 28	10.552	3.888		0	–
May 29 – Jul 29	25.666	6.308	–		–
Jul 30 – Aug 31	15.888	1.964	–	–	–
Sep 1 – Sep 30	11.662	8.331	–	–	0.595 (Sep 3 – Dec 38)
Oct 1 – Nov 30	17.117	25.170	–	–	
Dec 1 – Dec 31	7.378	14.142	–	–	
Jan 1 – Feb 28	11.901	29.256	–	–	–
	<b>116.945<sup>13</sup></b>	<b>113.782</b>	<b>40.959</b>	<b>0</b>	<b>0.595</b>
		<b>155.335 (Base Flow Volume)</b>			
		<b>282.280 (Friant Release Volume)</b>			

<sup>13</sup> In recent years, Holding Contract demands have been higher than assumed under Exhibit B of the Settlement, in which case, flows at Friant are increased to achieve the Gravelly Ford Flow Target.

<sup>14</sup> Buffer Flow volumes are based on actual releases, and are not an allocated volume per se.

## Remaining Flexible Flow Volume

The amount of water remaining for scheduling is the volume of flows released from Friant Dam in excess of releases required to meet Holding Contract demands, less past releases. Table 8 tracks these balances. The releases to date volumes are derived from quality-assurance/quality-control daily average data when available, and partly from provisional data posted to CDEC, and thus may have future adjustments. This may affect the remaining flow volume as well.

**Table 8 — Estimated Restoration Flow Volume Remaining and Released to Date**

Flow Account		Yearly Allocation <sup>15</sup> (TAF)	Released to Date <sup>16</sup> (TAF)	Remaining Flow Volume (TAF)
Base Flows	Continuity Flow Account (Mar 1 — Feb 28)	113.781	5.046	108.735
	Spring Flexible Flows (Mar 1 – Apr 30)	40.959	0	40.959
	Riparian Recruitment Flows (May 1 — Jul 29)	0	0	0
	Fall Flexible Flows (Oct 1 – Nov 30)	0.595	0	0.595
Unreleased Restoration Flows (Sales and Exchanges)		—	0	0
Unreleased Restoration Flows (Returned Exchanges)		—	0	0
Purchased Water		—	0	0
<b>Totals:</b>			<b>5.046</b>	<b>150.289</b>

<sup>15</sup> These Flow Volumes assume no channel constraints, as measured at Gravelly Ford.

<sup>16</sup> As of 3/18/2020

## Operational Constraints

Operating criteria, such as channel conveyance capacity, ramping rate constraints, scheduled maintenance, reservoir storage, contractual obligations, and downstream seepage concerns, may restrict the release of Restoration Flows. Table 9 summarizes known 2020 operational constraints.

**Table 9 — Summary of Operational Constraints**

Constraint	Period	Flow Limitation
Levee Stability	Currently in effect	1,210 cfs in Reach 2B
	Currently in effect	1,070 cfs in Eastside Bypass
Channel Conveyance / Seepage Limitation	Currently in effect, see latest Flow Bench Evaluation for precise values	Reach 2A: 800 – 820 cfs @ GRF
		Reach 3: 850 cfs @ MEN
		Reach 4A: 260 – 300 cfs @ SDP
Merced NWR weir Removal	June – September 2020	100 cfs 3-day average flow rate in Eastside Bypass

The Draft 2020 Channel Capacity Report identifies a maximum flow in Reach 2B of 1,210 cfs due to levee stability constraints. This results in a maximum release from Friant Dam between 1,310 cfs and 1,540 cfs depending on the time of year. The 2020 Restoration Year Channel Capacity Report also identifies a maximum flow in the Middle Eastside Bypass of 1,070 cfs due to levee stability constraints. These values are unchanged from 2019.

In 2020, multiple flow benches were conducted to verify expected seepage thresholds in Reach 2A and Reach 3. Analysis revealed a seepage limitation of 800 to 820 cfs in Reach 2A (measured at the GRF gauge) and 850 cfs in Reach 3 (measured at the MEN gauge). These seepage limitations fluctuate with prevailing groundwater conditions and may be slightly lower or higher at a given time. The limitation in Reach 3 must accommodate both Restoration Flows and diversion to Arroyo Canal, thus Reach 3 may be the limiting reach in certain times of the year. SJRRP will coordinate with the Restoration Administrator on specific flow schedules that are close to these limits. Flow – groundwater relationships from October 2019 through January 2020 were examined to determine a new seepage limitation in Reach 4A. For the current Reach 4A seepage limitation, wells installed in 2017 and later were incorporated into the analysis. Inclusion of these additional data points revealed that the seepage limitation is a lower flow rate than previously expected. Ongoing examination of a flow bench conducted in late February has not been completed, and when resolved may provide a narrower range of values for the seepage limitation in Reach 4A.

Reclamation will inform the Restoration Administrator of any changes to groundwater conditions that may result in a reduction in scheduled Restoration Flows, will implement monitoring of groundwater conditions as necessary, and will adjust Friant Dam releases and/or Mendota Pool

recapture (as preferred by the Restoration Administrator) to stay within seepage and channel capacity constraints.

Removal of the Merced National Wildlife Refuge weir is expected to take place between June and September. Based on the current information, a limitation of 100 cfs is expected. This limitation is based on a 3-day running average, allowing short period excursions of up to 120 cfs. This timing and rate of this flow limitation may be refined closer to the project period.

## 2020 Allocation History

The Restoration Allocation will be adjusted multiple times between the date of the initial allocation and the final allocation; issuances will generally take place on a monthly schedule but may also be issued based on rapidly changing hydrologic conditions. The next Restoration Allocation is scheduled to be issued between April 10 and April 20. However, because the current allocation is at the very lower limit of a Dry year type, an allocation would be updated before April 10 if the forecast falls below the 670 TAF threshold. The Restoration Administrator is responsible for contingency planning and managing releases to stay within the current allocation. Table 10 summarizes the Allocation History for this Restoration Year.

**Table 10 — Allocation History**

Allocation Type	Issue Date	Forecast Blending Applied	Unimpaired Inflow Forecast (at forecast exceedance)	Restoration Allocation at Gravelly Ford	Restoration Flows and URFs Released
Initial	January 16, 2020	20/80	928 TAF (@ 75%)	212.909 TAF	0 (thru 1/16/20)
Updated	February 7, 2020	10/90	664 TAF (@ 75%)	70.919 TAF	0 (thru 2/05/20)
Updated	February 19, 2020	20/80	506 TAF (@ 90%)	70.919 TAF	0 (thru 2/18/20)
Updated	March 20, 2020	10/90	670 TAF (@ 75%)	155.335 TAF	0 (thru 3/18/20)

## Appendix A: Abbreviations, Acronyms, and Glossary

af	acre–feet
ARS	USDA Agricultural Research Service
CALSIM	California Statewide Integrated Model
CCID	Central California Irrigation District
CDEC	California Data Exchange Center
cfs	cubic feet per second
CVP	Central Valley Project
Delta	Sacramento–San Joaquin Delta
DWR	California Department of Water Resources
ESP	Ensemble Streamflow Prediction
Exhibit B	Exhibit B of the Settlement depicting Default Hydrograph
GRF	Gravelly Ford Flow Gauge
Guidelines	Restoration Flow Guidelines
LSJLD	Lower San Joaquin Levee District
NASA	National Aeronautics and Space Administration
NWS	National Weather Service
QA/QC	Quality Assurance/Quality Control (i.e. finalized)
Reclamation	U.S. Department of the Interior, Bureau of Reclamation
Restoration Year	the cycle of Restoration Flows, March 1 through February 28/29
RWA	SJRRP Reclaimed Water Account
Secretary	U.S. Secretary of the Interior
Settlement	Stipulation of Settlement in <i>NRDC, et al., v. Kirk Rodgers, et al.</i>
SJREC	San Joaquin River Exchange Contractors
SJRRP	San Joaquin River Restoration Program
SLCC	San Luis Canal Company
TAF	thousand acre–feet
URF	Unreleased Restoration Flows
WSI	DWR Water Supply Index
WY	water year, October 1 through September 30



## Appendix B: Previous Year (2019) Flow Accounting

**Table B** — Restoration Flow Accounting and Unreleased Restoration Flows, and Holding Contracts, for the period February 2019 through February 2020. Flood management releases to San Joaquin River occurred during March, April, May, June, and July. This accounting includes 1.905 TAF that was generated in the 2019 Restoration Year and advanced into the final days of February 2019 (to the 2018 Restoration Year) and a flood spill of 22.509 TAF of URFs in July.

Flow Period	Gravelly Ford 5 cfs requirement (TAF)	Released Restoration Flow Volumes (TAF)							URFs (TAF)
		Spring Flexible Flow	Summer Base Flow	Fall Flexible Flow	Winter Base Flow	Riparian Recruitment Flow	Buffer Flow	Flexible Buffer Flow	
Feb 1 – Feb 28	–	1.905	–	–	–	–	–	–	–
Mar 1 – Mar 31	15.886	20.291	–	–	–	–	0	–	138.949
Apr 1 – Apr 30	0.276	21.683	–	–	–	–	0	–	80.000
May 1 – May 31	44.031	5.708	9.838	–	–	17.799	0	0	80.006
Jun 1 – Jun 30	10.102	–	9.164	–	–		0		23.999
Jul 1 – Jul 31	7.462	–	7.379	–	–		0		26.509
Aug 1 – Aug 31	10.873	–	11.633	–	–		0		14.244
Sep 1 – Sep 30	11.413	–	11.623	–	–	–	0	–	
Oct 1 – Oct 31	11.117	–	–	12.732	–	–	0	0	–
Nov 1 – Nov 30	10.364	–	–	13.896	–	–	0		–
Dec 1 – Dec 31	9.429	–	–	14.392	–	–	0		–
Jan 1 – Jan 31	9.749	–	–	–	15.602	–	0	–	–
Feb 1 – Feb 28	11.060	0	–	–	17.153	–	0	–	2.053
		<b>19.587</b>	<b>49.637</b>	<b>41.020</b>	<b>32.755</b>	<b>17.799</b>			
		<b>190.799</b>					<b>0.000</b>		<b>365.760</b>
	<b>151.761</b>	<b>190.799</b>							
		<b>556.559</b> (2019 Allocation: 556.542 + 0 Returned Exchange = error of 0.017 TAF)							
		<b>708.320</b>							

# Appendix C: History of Millerton Unimpaired Runoff

**Table C — Water Year Totals in Thousand Acre-Feet**

Water Year <sup>1</sup>	Unimpaired Runoff <sup>2</sup> (Natural River)	SJRRP Water Year Type <sup>3</sup>	Water Year <sup>1</sup>	Unimpaired Runoff <sup>2</sup> (Natural River)	SJRRP Water Year Type <sup>3</sup>	Water Year <sup>1</sup>	Unimpaired Runoff <sup>2</sup> (Natural River)	SJRRP Water Year Type <sup>3</sup>
1931	480.2	Critical-High	1963	1,945.266	Normal-Wet	1995	3,876.370	Wet
1932	2,047.4	Normal-Wet	1964	922.351	Dry	1996	2,200.707	Normal-Wet
1933	1,111.4	Normal-Dry	1965	2,271.191	Normal-Wet	1997	2,817.670	Wet
1934	691.5	Dry	1966	1,298.792	Normal-Dry	1998	3,160.759	Wet
1935	1,923.2	Normal-Wet	1967	3,233.097	Wet	1999	1,527.040	Normal-Wet
1936	1,853.3	Normal-Wet	1968	861.894	Dry	2000	1,735.653	Normal-Wet
1937	2,208.0	Normal-Wet	1969	4,040.864	Wet	2001	1,065.318	Normal-Dry
1938	3,688.4	Wet	1970	1,445.837	Normal-Dry	2002	1,171.457	Normal-Dry
1939	920.8	Dry	1971	1,416.812	Normal-Dry	2003	1,449.954	Normal-Dry
1940	1,880.6	Normal-Wet	1972	1,039.249	Normal-Dry	2004	1,130.823	Normal-Dry
1941	2,652.5	Wet	1973	2,047.585	Normal-Wet	2005	2,826.872	Wet
1942	2,254.0	Normal-Wet	1974	2,190.308	Normal-Wet	2006	3,180.816	Wet
1943	2,053.7	Normal-Wet	1975	1,795.922	Normal-Wet	2007	684.333	Dry
1944	1,265.4	Normal-Dry	1976	629.234	Critical-High	2008	1,116.790	Normal-Dry
1945	2,134.633	Normal-Wet	1977	361.253	Critical-Low	2009	1,455.379	Normal-Wet
1946	1,727.115	Normal-Wet	1978	3,402.805	Wet	2010	2,028.706	Normal-Wet
1947	1,121.564	Normal-Dry	1979	1,829.988	Normal-Wet	2011	3,304.824	Wet
1948	1,201.390	Normal-Dry	1980	2,973.169	Wet	2012	831.582	Dry
1949	1,167.008	Normal-Dry	1981	1,067.757	Normal-Dry	2013	856.626	Dry
1950	1,317.457	Normal-Dry	1982	3,317.171	Wet	2014	509.579	Critical-High
1951	1,827.254	Normal-Wet	1983	4,643.090	Wet	2015	327.410	Critical-Low
1952	2,840.854	Wet	1984	2,042.750	Normal-Wet	2016	1,300.986	Normal-Dry
1953	1,226.830	Normal-Dry	1985	1,135.975	Normal-Dry	2017	4,395.400	Wet
1954	1,313.993	Normal-Dry	1986	3,031.600	Wet	2018	1,348.979	Normal-Dry
1955	1,161.161	Normal-Dry	1987	756.853	Dry	2019	2,734.772	Wet
1956	2,959.812	Wet	1988	862.124	Dry			
1957	1,326.573	Normal-Dry	1989	939.168	Normal-Dry			
1958	2,631.392	Wet	1990	742.824	Dry			
1959	949.456	Normal-Dry	1991	1,027.209	Normal-Dry			
1960	826.021	Dry	1992	807.759	Dry			
1961	647.428	Critical-High	1993	2,672.322	Wet			
1962	1,924.066	Normal-Wet	1994	824.097	Dry			

<sup>1</sup> Water year is from Oct 1 through Sept 30, for example the 2010 water year began Oct 1, 2009. Unimpaired Runoff is based on Reclamation calculations, and hypothetical water year types are shown here; actual Restoration water year types are based on the final allocation, which may differ slightly from the calculated water year total.

<sup>2</sup> Also known as “Natural River” or “Unimpaired Inflow into Millerton” – This is the total runoff that would flow into Millerton Lake if there were no dams or diversions upstream. There was a lower level of precision prior to 1945.

<sup>3</sup> The six SJRRP Water Year Types are based on unimpaired inflow. Critical-Low=<400 TAF, Critical-High=400-669.999 TAF, Dry=670-929.999 TAF, Normal-Dry 930-1449.999, Normal-Wet 1450-2500, Wet>2500

## Appendix D: Final Restoration Allocations and Error

Table D — History of Restoration Allocations

Year	Type	Date of Final Allocation Issuance	Natural River Forecast in Final Allocation (TAF)	Restoration Allocation in Final Issuance (TAF)	Observed Natural River on Sep. 30 (TAF)	Error (Natural River / Allocation)
2009	Interim Flows			261.5	1,455.379	—
2010	Interim Flows			98.2	2,028.706	—
2011	Interim Flows			152.4	3,304.824	—
2012	Interim Flows			183	831.582	—
2013	Interim Flows			65.5	856.626	—
2014	Restoration Flows	Mar 3	518	0 <sup>1</sup>	509.579	+8.421 / 0 <sup>1</sup>
2015	Restoration Flows	Sep 28	327	0	327.410	-0.410 / 0
2016	Restoration Flows	Sep 30	1300.986	263.295	1,300.986	0 / 0
2017	Restoration Flows	Jul 10	4,444	556.542	4,395.400	+48.600 / 0
2018	Restoration Flows	May 22	1,427	280.258	1,348.979	+78.021 / +10.503
2019	Restoration Flows	May 20	2,690	556.542	2,734.772	-44.772 / 0.017

<sup>1</sup> No water was provided under this Critical-High designation due to Friant Dam releases for the Exchange Contract.